

ProCurve Wireless Access Point 10ag

The ProCurve Wireless Access Point 10ag is ideal for small enterprise networks that need to deploy wireless connectivity quickly and easily with minimal investment. The Wireless Access Point 10ag can be configured in just minutes using the intuitive Web Managed interface. The ProCurve Wireless Access Point 10ag also supports IEEE 802.11a, 802.11b, and 802.11g clients simultaneously via its dual IEEE 802.11a and 802.11b/g radios. The Wireless Access Point 10ag can be wall-mounted or placed on a flat surface and has the option to be powered by Power over Ethernet (PoE), allowing for maximum location flexibility.



ProCurve Wireless Access Point 10ag NA (J9140A)



ProCurve Wireless Access Point 10ag WW (J9141A)

ProCurve Wireless Access Point 10ag

Features and benefits

Mobility

- **Interoperability:** Wi-Fi Alliance certifications including IEEE 802.11a, 802.11b, 802.11g Wi-Fi, and WPA2 to help ensure multivendor interoperability

Connectivity

- **Simultaneous IEEE 802.11a and 802.11g dual radio operation:** supports up to 64 wireless clients and provides backward compatibility for IEEE 802.11b wireless devices

Security

- **Choice of Wi-Fi Protected Access 2 (WPA2) or WPA:** locks out unauthorized wireless access by authenticating users prior to granting network access; robust Advanced Encryption Standard (AES) or Temporal Key Integrity Protocol (TKIP) encryption secures the data integrity of the wireless traffic
- **Supports up to 8 SSIDs:** permits network administrators to control user access to network resources based on user authentication and level of trusted security between the wireless user and the access point
- **IEEE 802.1X:** provides port-based user authentication with support for Extensible Authentication Protocol (EAP) MD-5, TLS, TTLS, and PEAP with choice of AES, TKIP, and static or dynamic WEP encryption for protecting wireless traffic between authenticated clients and the access point
- **RADIUS-based MAC authentication:** a wireless client is authenticated with a RADIUS server based on the MAC address of the client; this is useful for clients that have minimal or no user interface
- **RADIUS accounting support:** separate RADIUS accounting server support per SSID; provides detailed session, usage, and billing information for each client activity

- **MAC address lockout:** prevents configured particular MAC addresses from connecting to the network

- **Management password:** provides security so that only authorized access to the Web browser interface is allowed

Manageability

- **Intuitive Web interface:** enables simple management via an easy-to-use Web browser interface for access point configuration, monitoring, and administration
- **Integration with ProCurve Manager:** enables discovery and mapping via ProCurve Manager, available as a free download from the Web

Ease of use

- **Comprehensive LED display:** provides an at-a-glance view of status, activity, speed, and radio operation

Flexibility

- **Choice of power supply (standard AC power or IEEE 802.3af PoE):** provides location flexibility for where the access point is deployed. To use the Power over Ethernet (PoE) option, the access point must be connected to a PoE switch or PoE injector.
- **Deployment options:** access point can be mounted on a vertical wall or placed on a flat surface

Industry-leading warranty

- **Lifetime warranty :** for as long as you own the product, with next-business-day advance replacement (available in most countries)

Services

ProCurve Wireless Access Point 10ag NA

ProCurve Wireless Access Point 10ag

- 3-year, 4-hour onsite, 13x5 coverage for hardware (U4683E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (U4835E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6321E)
- 3-year, 24x7 SW phone support, software updates (UF792E)

ProCurve Wireless Access Point 10ag WW

- 3-year, 4-hour onsite, 13x5 coverage for hardware (U4683E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (U4835E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6321E)
- 3-year, 24x7 SW phone support, software updates (UF792E)

ProCurve Wireless Access Point 10ag



ProCurve Wireless Access Point 10ag NA (J9140A)



ProCurve Wireless Access Point 10ag WW (J9141A)

Specifications

Ports		
	1 RJ-45 auto-sensing 10/100 port (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Duplex: half or full	1 RJ-45 auto-sensing 10/100 port (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Duplex: half or full
Physical characteristics		
Dimensions	4.06(d) x 7.01(w) x 1.34(h) in. (10.3 x 17.8 x 3.4 cm)	4.06(d) x 7.01(w) x 1.34(h) in. (10.3 x 17.8 x 3.4 cm)
Weight	0.62 lb. (0.28 kg)	0.62 lb. (0.28 kg)
Memory and processor		
Processor	MIPS 4000 @ 220 MHz, 16 MB SDRAM, 2 MB flash ROM	MIPS 4000 @ 220 MHz, 16 MB SDRAM, 2 MB flash ROM
Environment		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C); PoE mode
Operating relative humidity	5% to 95% @ 104°F (40°C), non-condensing	5% to 95% @ 104°F (40°C), non-condensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	5% to 95% @ 158°F (70°C), non-condensing	5% to 95% @ 158°F (70°C), non-condensing
Altitude	up to 10000 ft. (3 km)	up to 10000 ft. (3 km)
Electrical characteristics		
Description	Voltage: 48 VDC (PoE); 12 VDC (power adapter)	Voltage: 48 VDC (PoE); 12 VDC (power adapter)
Maximum heat dissipation	25 / 33 BTU/hr (26.38 / 34.82 kJ/hr)	25 / 33 BTU/hr (26.38 / 34.82 kJ/hr)
Current	0.6 / 0.2 A	0.6 / 0.2 A
Power consumption	7 W	7 W
Frequency band and Operating channels		
FCC (US & Canada)	2.412 - 2.462 GHz (11 channels) 5.150 - 5.250 GHz (4 channels) 5.725 - 5.825 GHz (5 channels)	
European Union	2.412 - 2.472 GHz (13 channels) 5.150 - 5.350 GHz (8 channels) 5.470 - 5.725 GHz (11 channels)	
Japan	2.412 - 2.484 GHz (14 channels) 5.150 - 5.350 GHz (8 channels)	
China	2.412 - 2.472 GHz (13 channels) 5.725 - 5.825 GHz (5 channels)	
Singapore	2.412 - 2.472 GHz (13 channels) 5.150 - 5.350 GHz (8 channels) 5.725 - 5.825 GHz (5 channels)	
Taiwan	2.412 - 2.462 GHz (11 channels) 5.725 - 5.825 GHz (5 channels)	
Korea	2.412 - 2.472 GHz (13 channels) 5.150 - 5.350 GHz (8 channels) 5.725 - 5.825 GHz (4 channels)	
Australia	2.412 - 2.472 GHz (13 channels) 5.725 - 5.825 GHz (5 channels)	

ProCurve Wireless Access Point 10ag

Radio

FCC Part 15.247; FCC Part 15.407 (US); RSS-210 (Canada); EN 300 328; EN 301 893 (Europe); ARIB STD-T66; ARIB STD-T71; ARIB STD-33; RSS-Gen (Canada)

FCC Part 15.247; FCC Part 15.407 (US); RSS-210 (Canada); EN 300 328; EN 301 893 (Europe); ARIB STD-T66; ARIB STD-T71; ARIB STD-33; RSS-Gen (Canada)

Safety

UL 60950-1; CAN/CSA 22.2 No. 60950-1

IEC 60950-1; EN 60950-1

Emissions

FCC Part 15.107; EN 60601-1-2; EN 301 489-1; EN 301 489-17; FCC Part 15.109; ICES-003 (Canada)

FCC Part 15.107; EN 60601-1-2; EN 301 489-1; EN 301 489-17; FCC Part 15.109; ICES-003 (Canada)

RF Exposure

FCC Bulletin OET-65C; IEEE C95.1; RSS-102

EN 50385

Management

ProCurve Manager; Web browser

ProCurve Manager; Web browser

Notes

Antennas - Integral 2.4 GHz 1.8 dBi diversity antennas; 5 GHz 1.8 dBi diversity antennas

ProCurve Wireless Access Point 10ag

ProCurve Wireless Access Point 10ag NA (J9140A)

Radio characteristics: 802.11g

Data rate	54 Mbps	48 Mbps	36 Mbps	24 Mbps	18 Mbps	12 Mbps	9 Mbps	6 Mbps
Receiver sensitivity	-71 dBm	-73 dBm	-77 dBm	-80 dBm	-85 dBm	-87 dBm	-88 dBm	-89 dBm
Transmit power	19 dBm	20 dBm	20 dBm	20 dBm	20 dBm	20 dBm	20 dBm	20 dBm

802.11b

Data rate	11 Mbps	5.5 Mbps	2 Mbps	1 Mbps
Receiver sensitivity	-86 dBm	-88 dBm	-90 dBm	-94 dBm
Transmit power	20 dBm	20 dBm	20 dBm	20 dBm

802.11a

Data rate	54 Mbps	48 Mbps	36 Mbps	24 Mbps	18 Mbps	12 Mbps	9 Mbps	6 Mbps
Receiver sensitivity	-72 dBm	-73 dBm	-79 dBm	-82 dBm	-85 dBm	-87 dBm	-89 dBm	-90 dBm
Transmit power	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm

ProCurve Wireless Access Point 10ag WW (J9141A)

Radio characteristics: 802.11g

Data rate	54 Mbps	48 Mbps	36 Mbps	24 Mbps	18 Mbps	12 Mbps	9 Mbps	6 Mbps
Receiver sensitivity	-71 dBm	-73 dBm	-77 dBm	-80 dBm	-85 dBm	-87 dBm	-88 dBm	-89 dBm
Transmit power	17.5 dBm	17.5 dBm	17.5 dBm	17.5 dBm	17.5 dBm	17.5 dBm	17.5 dBm	17.5 dBm

802.11b

Data rate	11 Mbps	5.5 Mbps	2 Mbps	1 Mbps
Receiver sensitivity	-86 dBm	-88 dBm	-90 dBm	-94 dBm
Transmit power	17 dBm	17 dBm	17 dBm	17 dBm

802.11a

Data rate	54 Mbps	48 Mbps	36 Mbps	24 Mbps	18 Mbps	12 Mbps	9 Mbps	6 Mbps
Receiver sensitivity	-72 dBm	-73 dBm	-79 dBm	-82 dBm	-85 dBm	-87 dBm	-89 dBm	-90 dBm
Transmit power	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm	18 dBm

ProCurve Wireless Access Point 10ag

Standards and Protocols

General Protocols

IEEE 802.3 Type 10BASE-T
IEEE 802.3af Power over Ethernet
IEEE 802.3u 100BASE-X

Mobility

IEEE 802.11a High Speed

Physical Layer in the 5 GHz Band
IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band
IEEE 802.11g Further Higher Data Rate Extension in the 2.4

GHz Band

Security

IEEE 802.1X Port Based Network Access Control
WPA (Wi-Fi Protected Access)

© 2007 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



10/23/2007
To learn more, visit www.procurve.com
Information is subject to change without notice